



MATERIAL SAFETY DATA SHEET

CoorsTek, 600 Ninth Street, Golden, Colorado 80401	EMERGENCY TELEPHONE NO: (303) 278-4000		
TRADE NAME: Zirconia Ceramic	MSDS NUMBER: 02	DATE OF ISSUE: June 9, 1992	
CHEMICAL NAME: Sintered Zirconia Ceramic	SYNONYMS: TTZ - All		
PREPARED BY: CoorsTek, Inc.	REVISION: 03	REVISION DATE: January 2001	REVIEWED BY: Environmental, Health and Safety

1. INGREDIENTS

MATERIAL	PERCENT	ACGIH (TLV)	OSHA (PEL)
1. Zirconium Oxide (CAS #1314-23-4)	> 96	10 mg/m ³ (STEL) 5 mg/m ³ (T) (as Zr)	5 mg/m ³ (T) (as Zr)
2. Amorphous Phase (See Comment 1, Section II)	< 4	Not Established	Not Established
<p>All values are Time-Weighted Averages STEL = Short Term Exposure Limit T = Total Particulate Matter R = Respirable Fraction of Particulate Matter</p>			

2. PHYSICAL DATA

APPEARANCE: White inert solid	ODOR: None	MELTING POINT: 5000°F	SPECIFIC GRAVITY: Approximately 5.8
VAPOR DENSITY (AIR = 1): NA	% VOLATILE BY VOLUME: 0	BULK DENSITY: NAIF	BOILING POINT: 4000°F
VAPOR PRESSURE: NA	% SOLUBILITY (H ₂ O): Negligible	EVAPORATION RATE (BuOAC = 1): NAIF	OTHER: NAIF

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD: NA
FLAMMABLE LIMITS LEL: NA UEL: NA
EXTINGUISHING MEDIA: Will not burn. Select media that is appropriate for fighting surrounding fire.
SPECIAL FIRE-FIGHTING PROCEDURES: Use NIOSH approved self-contained breathing apparatus with full face-piece operated in pressure demand or other positive pressure mode. Wear full fire-fighting protective clothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS Not an explosion hazard.

4. HEALTH HAZARD DATA

LD50 ORAL (INGESTION) NAIF	LD50 DERMAL (SKIN CONTACT) NAIF	LD50 (INHALATION) NAIF
PRIMARY ROUTE OF EXPOSURE Inhalation		
EFFECTS OF OVEREXPOSURE: FIRED OR SINTERED SOLID MATERIAL HAS NO KNOWN HEALTH HAZARD. ACUTE: High dust concentrations may cause mechanical eye irritation and upper respiratory irritation. Prolonged skin contact with dust may result in dryness. CHRONIC: Chronic exposure to dusts may cause pneumoconiosis. There are no known medical conditions aggravated by exposure to this product.		

5. EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Move to area free from risk of further exposure. Administer oxygen or artificial respiration, as needed. Get medical attention.

Eye Contact: Flush with tepid water for at least 15 minutes while holding eyelids open. Seek medical attention if irritation develops.

Skin Contact: Wash affected areas with soap and water. Seek medical attention if irritation develops.

Ingestion: Not a likely route of exposure. If large amounts of product are ingested, give two glasses of water and get prompt medical attention. Never give anything by mouth to an unconscious person.

6. PHYSICAL HAZARDS

None known.

7. SPECIAL PROTECTION INFORMATION

VENTILATION:

If dust is generated during processing or use, local exhaust should be provided to maintain exposures below the limits cited in Section 1. Design details for local exhaust ventilation systems may be found in the the latest edition of "Industrial Ventilation: A Manual of Recommended Practices" published by ACGIH Committee on Industrial Ventilation, P.O. Box 16153, Lansing, MI 48910. The need for local exhaust ventilation should be evaluated by a professional industrial hygienist. Local Exhaust systems should be designed by a professional engineer.

RESPIRATORY:

If airborne concentrations may exceed the exposure limits outlined in Section 1, use a NIOSH/MSHA approved respirator for dusts and mists with an exposure limit of not less than 0.05 mg/M³. If exposures exceed 10 times the recommended limits, consult a professional industrial hygienist, or your respiratory equipment supplier, about the selection of the proper equipment. The evaluation of the need for respiratory protection should be determined by a professional industrial hygienist.

EYE PROTECTION:

Safety glasses are recommended.

PROTECTIVE GLOVES:

Wear any polymer gloves if prolonged exposure to powder is expected.

ALL CHEMICALS SHOULD BE HANDLED SO AS TO PREVENT EYE CONTACT AND EXCESSIVE OR REPEATED SKIN CONTACT. APPROPRIATE EYE AND SKIN PROTECTION SHOULD BE EMPLOYED. INHALATION OF DUSTS AND VAPORS SHOULD BE AVOIDED. PROPER PERSONAL PROTECTVIE EQUIPMENT SELECTION SHOULD FOLLOW THE RECOMMENDATIONS PROVIDED IN THE HAZARD ANALYSIS DONE FOR THE TASK INVOLVED, OR AS DETERMINED BY A PROFESSIONAL INDUSTRIAL HYGIENIST.

8. CHEMICAL REACTIVITY

CONDITIONS CAUSING INSTABILITY:

Stable. None known.

INCOMPATIBILITY (MATERIALS TO AVOID):

None known.

HAZARDOUS DECOMPOSITION PRODUCTS:

May include oxides of aluminum at high temperatures.

SPECIAL SENSITIVITY:

None known.

9. STORAGE INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in a cool, dry area. Any dust generated during handling or processing should be removed by wet mopping or vacuuming. Avoid breathing dusts.

10. SPILL, LEAK, AND DISPOSAL INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Secure area and obtain necessary personal protective equipment. Scoop up material and place in appropriate containers for reuse or disposal. Do not allow material to enter sewer or waterways. Wet mopping or vacuuming may clean up small amounts.

EPA RCRA ID NUMBER:

N/A

WASTE DISPOSAL METHOD:

This material, if discarded, is not defined as hazardous under 40 CFR 261. Disposal in a landfill in accordance with applicable federal, state, and local laws or regulations is recommended.

11. ADDITIONAL COMMENTS

1. This product contains the following ingredients which are listed as Special Health Hazard Substances by the State of New Jersey: None
2. This product contains the following ingredients which are listed as hazardous substances under the State of New Jersey Right-To-Know legislation: Magnesium Oxide.
3. This product contains the following ingredients which are listed as Special Hazardous Substances by the Commonwealth of Pennsylvania: Magnesium Oxide (regulated under a synonym).
4. This product contains the following ingredients which are listed as Extraordinarily Hazardous Substances by the Commonwealth of Massachusetts: None
5. This product contains the following ingredients listed under Proposition 65 of the State of California: Magnesium Oxide
6. This product contains the following ingredients listed as a CAL-OSHA Workplace Airborne Contaminant: Magnesium Oxide
7. This product contains the following ingredients listed on the Illinois Toxic Substances Disclosure to Employees List: Magnesium Oxide
8. This product contains the following ingredients listed on the Florida Toxic Substance in Workplace: Magnesium Oxide
9. This product contains the following ingredients regulated as a Texas Air Contaminant with the Health Effects Screening Level: Magnesium Oxide (regulated under a synonym)
10. Pursuant to Section 313, SARA Title III, this product contains the following reportable substances: None
11. OSHA Hazard Communication Categories: Irritant, Eye Hazard, and Lung Hazard.
12. SARA: Fire - No; Pressure - No; Reactive - No; Acute - Yes; Chronic - Yes.
13. No DOT labels are required, no DOT Hazard I.D. Number has been assigned, and no DOT shipping restrictions apply.
14. Judgements as to the suitability of the information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore, although reasonable care has been taken in the preparation of such information, CoorsTek extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.

Not Est. = Not Established

NAIF = No Applicable Information Found

NA = Not Applicable