

POLYBAC #519 Large Beads

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name POLYBAC #519 w/Large Beads - PART B

POLYGEM INC. Company

PO Box 609

West Chicago, Illinois 60185

Telephone 630 231 5600

630 231 5604 (Fax Line)

USA +1 800 535 5053 **Emergency telephone number**

International 01 352 323 3444

SECTION 2. HAZARDS IDENTIFICATION

mixture Classification according to the **Regulation (EC) No. 1272/2008**

2.1 Classification of the substance or Acute Dermal Toxicity Category 4 Acute Oral Toxicity Category 4 Skin Sensitization Category 1 Skin Corrosion/irritation Category 18

Chronic Aquatic Toxicity Category 2

Classification according to the Regulation

Directive 199/45/EC

[Xn] Harmful, [C] Corrosive, [N] Dangerous to the Environment

INFORMATION CONCERNING PARTICULAR HAZARDS FOR **HUMAN AND ENVIRONMENT**

> **Product description** This product is gray heavy paste with a sweet amine odor

Health hazards Corrosive, Severe eye irritant; Respiratory Irritant, may cause skin sensitization.

Flammability hazards This product is flammable above its flashpoint of 380° F (195° C)

Reactivity hazards None known

Environmental hazards The environmental effects of this product have not been investigated; however it is not

expected to cause significant adverse effects.

Emergency considerations Emergency responders must wear proper personal protective equipment (and have

appropriate fire suppression equipment) suitable for the situation to which they are

responding.



POLYBAC #519 Large Beads

SECTION 2. HAZARDS IDENTIFICATION, CONTINUED

GHS LABEL ELEMENTS

Hazard symbols



Signal word Danger

Hazard statements H302: Harmful if swallowed

> H313: May be harmful in contact with skin H317: May cause an allergic skin reaction H335: May cause respiratory irritation

PRECAUTIONARY STATEMENTS P260: Do not breathe dust/fume/gas/mist/vapors/spray

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

Response Statements

P337+P313: If eye irritation persists: seek medical advice/attention.

P370+P378 - In case of fire: Use appropriate media for extinction.

P302+P353 - IF ON SKIN: Wash with plenty of soap and water for extinction.

P391: Collect spillage

P403±P235: Store in well ventilated place. Keep cool.

P501: Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

HMIS rating

CHEMICAL NAME	
Health	3
Flammability	1
Physical hazard	0
Personal protection	F

2.3 Other Hazards

None Known

HEALTH-3. FLAMMABILITY-1. REACTIVITY-0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not "hazardous" per the OSHA standard.



POLYBAC #519 Large Beads

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS	OSHA PEL*	ACGIH TLV*	WT%
Diaminodiphenlymethane	101-77-9	0.01 ppm (S) 10 ppb.	N/E	2
Modified Aliphatic Polyamine	T/S	N/E	N/E	5
Diethylenetnamine	111-40-0	1 ppm ACGIH (S)	N/E	1
Aluminum Oxide	1344-28-1	N/E	N/E	50-60
Silicon Carbide	409-21-2	N/E	N/E	10
Calcium Carbonate	1317-65-3	N/E	N/E	10
Silica, amorphous, fumed, crystalline free	112945-52-5	N/E	N/E	2

^{*} ALL INGREDIENTS ARE REGISTERED ON TSCA.

Emergency overview

Mild or moderate eye irritation.

May cause skin irritation.

Harmful if swallowed.

POTENTIAL HEALTH EFFECTS

Eye contact Mild or moderate irritation, possible minor temporary cornea injury.

Skin contact May cause skin irritation on prolonged or repeated exposure.

Skin absorption Not considered toxic.

Inhalation May cause nasal irritation, central nervous system depression or lung injury.

Chronic effects of over exposure None

SECTION 4. FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES

Eye contact Flush with plenty of water and get medical attention. Keep eye lids apart. Wash

within 1 minute of contact for maximum results.

Skin contact Promptly wipe clean with paper or cloths and wash with soap and water. Remove

contaminated clothing before reuse. Attention should be paid to hair, nose and eyes.

Inhalation In case of exposure to high concentration of vapor or mist, remove person

to fresh air. If large amounts are swallowed, induce vomiting. Seek medical

attention. May cause burns to mouth and throat.

^{*} Unless otherwise noted, all PEL and TL V Values are reported as 8 hour time weighted averages (TWA).

^{*} T/S - Trade Secret



POLYBAC #519 Large Beads

SECTION 4. FIRST AID MEASURES, CONTINUED

Ingestion If large amounts are swallowed, induce vomiting. Seek medical attention. May

cause burns to mouth and throat.

Primary routes of entry Inhalation, ingestion, skin, and eye contact.

This product does not contain 0.1% or more of any substance which is listed as a Carcinogenicity

carcinogen by NTP, IARC or OSHA.

SECTION 5. FIRE FIGHTING MEASURES

Flash point 234° F

Test method Setaflash Closed Cup

Lower flammability limit N/A Upper flammability limit N/A

Recommended extinguishing media Water, Foam, Carbon Dioxide, Dry Chemicals, or Fog.

Special fire fighting procedures Firefighters should wear protective goggles and self contained breathing

apparatus to avoid inhalation of smoke or vapors. Remove all ignition sources.

Unusual fire or explosion hazards May produce hazardous fumes or hazardous decomposition products, such as

> (conditions to avoid) carbon dioxide, carbon monoxide, hydrogen sulfide, oxides of sulfur and nitrogen.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Special protection Exposure to the spilled material may be irritating or harmful. Follow personal

protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, the

area in which the spill occurred.

Steps to be taken in case material is Ventilate the area. Absorb spill with suitable absorbent material and place into

released or spilled a closed container. Prevent material from entering waterways. Wear protective

equipment during cleanup. Use eye and skin protection.

Transport emergency phone number (INFOTRAC) 1-800-535-5053

SECTION 7. HANDLING AND STORAGE

Handling Harmful or irritation material. Avoid contact and avoid breathing the material

Use only in a well ventilated area.

Storage Store in a cool, dry place.



POLYBAC #519 Large Beads

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection If vapor or mist 1s generated and the occupational exposure limit is exceeded,

use appropriate NIOSH/MSHA approved self-contained breathing equipment or a full face respirator. Respirators should be selected by and used following requirements found in OSHA's respirator standards (29 CFR 1910134). Not

required for properly ventilated area.

Ventilation Local exhaust and general ventilation is recommended.

Hand protection Nitrile Rubbers gloves

Eye protection Wear safety glasses with side shields when handling this product. Wear

additional eye protection such as chemical splash goggles and/or face shield when the possibility exits for eye contact with splashing or spraying liquid, or

airborne material. Have an eye wash station available.

Skin and body protection Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt.

An apron may be appropriate if splashing can occur.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Gel

Color Gray

Odor Amine odor

Weight by gallon 14 lbs.

Solids (% by weight) 100

V.O.C. O g/L

Boiling range 335 F

Melting point N/E

Density 1.04

Percent volatile Not volatile

Vapor density (air=1) N/D

Vapor pressure (mm Hg) N/E

Evaporation rate N/A

Water miscibility <0.1%



POLYBAC #519 Large Beads

SECTION 10. STABILITY AND REACTIVITY

Stability Stable

Incompatibility Strong oxiders, epoxy resin, and amine mixtures especially when hot

Hazardous polymerization Will not occur

Hazardous decomposition products Oxides of Carbon and Phenolics under burning conditions

Conditions to avoid Heat and warm storage

SECTION 11. TOXICOLOGICAL INFORMATION

CHEMICAL NAME LD50/LC50

Epoxy resin Not established

SECTION 12. ECOLOGICAL INFORMATION

Overview No ecological information available.

SECTION 13. DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

(Consult Bill of Lading for transportation information)

DOT CORROSIVE LIQUID N.O.S.

IATA CORROSIVE LIQUID N.O.S.



POLYBAC #519 Large Beads

SECTION 15. REGULATORY INFORMATION

OSHA Hazard Communication Standard N/A

(29 CFR 1910.1200) Hazard Class(es)

SARA Hazard Classification SARA Title III Regulations (40 CFR 370): N/A

SARA Section 313 Listed Ingredients This material does not contain any substance which is subject to the reporting

requirements of 40 CFR 372.

DOT Proper Shipping Name Corrosive Liquid N.O.S. (Diaminodiphenylmethane/Diethylene Triamine)

UN Number UN1760

SECTION 16. OTHER INFORMATION

This information is furnished without warranty, representation inducement or license of any kind, except that is accurate to the best of Polygem Inc. knowledge, or obtained from sources believed by Polygem Inc. to be accurate and Polygem Inc. does not assure any legal responsibility for use reliance upon the same. Customers are encouraged to conduct their own tests. Before using any product, please read its label.

Revision date 06/2015