



High-Performance Heating Igniters

Premium Ceramic Igniters



High-Performance Heating Igniters

CoorsTek igniter products deliver exceptionally dependable ignition in heating systems of every type. We work with all leading control manufacturers to supply state-of-the-art hot surface igniters for a wide variety of ignition systems. These include 24 V, 120 V, and 208/240 V control systems used in conjunction with CoorsTek igniter products.

- Positive ignition over a wide range of gas-air mixtures and conditions
- High physical and thermal strength
- Flexible design
- Easy mounting
- Large selection of standard terminals
- CSA design certified

Standard mounting configurations are available.



Our family of igniter products

Contact us for more information
 +1 303 271 7100 or info@coorstek.com

IGNITER FAMILY	TRADITIONAL IGNITERS		MINI-IGNITER™		DURAGLO™ IGNITER
MODEL NO.	201	271	401	601	901
Time to 980°C	34 sec.	17sec.	3 sec.	5 sec.	8 sec.
Room temperature resistance	45-400 Ohms	40-100 Ohms	1.0-6.0 Ohms	25-300 Ohms	20-100 Ohms
Temperature range:					
Minimum	1800°F/ 980°C @ 102 V		1895°F/ 1035°C @ 20.4 V	1800°F/980°C @ 102 V	1800°F/980°C @ 102 V
Maximum	3100°F/ 1705°C @ 132 V		2875°F/1580°C @ 26 V	2875°F/1580°C @ 132 V	2700°F/1480°C @ 132 V
Typical	2400-2650°F 1320-1455°C @ 120 V		2102 - 2650°F 1150 - 1455°C @ 24 V	2102 - 2650°F 1150 - 1455°C @ 120 V	2102 - 2550°F 1150 - 1400°C @ 120V
Steady-state current	3.50-5.0 Amps @ 132 V		1.0-2.2 Amps @ 24 V	0.4-1.2 Amps @ 120 V	0.4-1.2 Amps @ 120 V
Igniter material	recrystallized silicon carbide		proprietary ceramic composite		silicon nitride
Holder material	Standard and custom designs available in alumina, steatite or cordierite				
Lead wires	Length to suit (maximum 36")				
Control system	Compatible with all leading manufacturers' systems				

The chart is intended to illustrate typical properties. Property values vary with method of manufacture, size, and shape of part. Data contained herein is not to be construed as absolute and does not constitute a representation or warranty for which CoorsTek assumes legal responsibility. CoorsTek is a registered trademark of CoorsTek, Inc.



Americas
 +1 303 271 7100 tel
 +1 855 929 7100 toll free in USA
coorstek.com
info@coorstek.com

Europe
 +49 160 530 3768
infoeurope@coorstek.com

Japan
 +1 81 3 5437 8411
japaninfo@coorstek.com

China
 +86 21 6232 1125
info_shanghai@coorstek.com

Korea
 +82 31 613 2946
koreainfo@coorstek.com